

SAFETY DATA SHEET

EMP110/5140 W LED AS

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name EMP110/5140 W LED AS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Printing ink.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Electra Polymers Ltd
Roughway Mill,
Roughway Lane
Tonbridge
Kent TN11 9SG
UK
Tel: +44 1732 811118
Fax: +44 1732 811119
sds@electrapolymers.com

1.4. Emergency telephone number

Emergency telephone +44 (0)1732 811 118 (08.30 - 17.00 GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Repr. 2 - H361fd

Environmental hazards Aquatic Chronic 3 - H412

Human health The product contains small amounts of organic solvents. Considered to be a low inhalation hazard at normal workplace temperatures.

Environmental The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H412 Harmful to aquatic life with long lasting effects.

EMP110/5140 W LED AS

Precautionary statements	<p>P201 Obtain special instructions before use.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p>
Contains	Ethoxylated (3) trimethylolpropane triacrylate, Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide, PHENYL BIS(2,4,6-TRIMETHYLBENZOYL)-PHOSPHINE OXIDE
Supplementary precautionary statements	<p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB. May cause skin sensitisation or allergic reactions in sensitive individuals.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Methoxypropoxypropanol	10-30%
CAS number: 34590-94-8 EC number: 252-104-2 REACH registration number: 01-2119450011-60-XXXX	
Classification Not Classified	
Ethoxylated (3) trimethylolpropane triacrylate	5-10%
CAS number: 28961-43-5 EC number: 500-066-5	
Classification Eye Irrit. 2 - H319 Skin Sens. 1 - H317	
2,5-Furandione, polymer with ethenylbenzene, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	5-10%
CAS number: 67527-24-6	
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	

EMP110/5140 W LED AS

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	1-5%
CAS number: 75980-60-8	EC number: 278-355-8
Classification	
Skin Sens. 1B - H317	
Repr. 2 - H361fd	
Aquatic Chronic 2 - H411	
PHENYL BIS(2,4,6-TRIMETHYLBENZOYL)-PHOSPHINE OXIDE	1-5%
CAS number: 162881-26-7	EC number: 423-340-5
Classification	
Skin Sens. 1 - H317	
Aquatic Chronic 4 - H413	
2,6-di-tert-butyl-4-methylphenol	<0.1%
CAS number: 128-37-0	EC number: 204-881-4
	REACH registration number: 01-2119555270-46-XXXX
M factor (Acute) = 1	M factor (Chronic) = 1
Classification	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
2-BUTOXYETHYL ACETATE	<0.1%
CAS number: 112-07-2	EC number: 203-933-3
	REACH registration number: 01-2119475112-47-XXXX
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
HEPTANE	<0.1%
CAS number: 142-82-5	EC number: 205-563-8
M factor (Acute) = 1	M factor (Chronic) = 1
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

EMP110/5140 W LED AS

METHANOL	<0.1%
CAS number: 67-56-1	EC number: 200-659-6
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT SE 1 - H370	

ETHYLENEDIAMINE	<0.1%
CAS number: 107-15-3	EC number: 203-468-6
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Resp. Sens. 1 - H334	
Skin Sens. 1 - H317	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	No specific recommendations. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	Treat symptomatically.
Inhalation	No specific symptoms known. May cause respiratory irritation.
Ingestion	No specific symptoms known. May cause irritation.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals.
Eye contact	Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	May cause sensitisation by skin contact.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

EMP110/5140 W LED AS

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards None.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours and spray/mists. Wear protective clothing, gloves, eye and face protection.

Advice on general occupational hygiene Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and using the toilet. Remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Store in tightly-closed, original container. Protect from freezing and direct sunlight.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

EMP110/5140 W LED AS

8.1. Control parameters

Occupational exposure limits

Methoxypropoxypropanol

Long-term exposure limit (8-hour TWA): WEL 50 ppm 308 mg/m³
Sk

2,6-di-tert-butyl-4-methylphenol

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

2-BUTOXYETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 20 ppm 133 mg/m³
Short-term exposure limit (15-minute): WEL 50 ppm 332 mg/m³
Sk

HEPTANE

Long-term exposure limit (8-hour TWA): WEL 500 ppm
Short-term exposure limit (15-minute): WEL

METHANOL

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m³
Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m³
Sk

ETHYLENEDIAMINE

Long-term exposure limit (8-hour TWA): WEL 10 ppm(Sk) 25 mg/m³(Sk)
Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Methoxypropoxypropanol (CAS: 34590-94-8)

DNEL	Workers - Dermal; Long term systemic effects: 283 mg/kg Workers - Inhalation; Long term systemic effects: 308 mg/kg
PNEC	- Fresh water; 19 mg/l - marine water; 1.9 mg/l - Intermittent release; 190 mg/l - STP; 4168 mg/l - Sediment (Freshwater); 70.2 mg/l - Sediment (Marinewater); 7.02 mg/l - Soil; 2.74 mg/l

Ethoxylated (3) trimethylolpropane triacrylate (CAS: 28961-43-5)

DNEL	Industry - Dermal; Long term systemic effects: 0.8 mg/m ³
-------------	--

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (CAS: 75980-60-8)

DNEL	Industry - Inhalation; Long term systemic effects: 3.5 mg/m ³ Industry - Dermal; Long term systemic effects: 1 mg/m ³
PNEC	- Fresh water; 0.00353 mg/l - marine water; 0.000353 mg/l - Intermittent release; 0.0353 mg/l - Sediment (Freshwater); 0.29 mg/kg - Sediment (Marinewater); 0.029 mg/kg - Soil; 0.0557 mg/kg

EMP110/5140 W LED AS

PHENYL BIS(2,4,6-TRIMETHYLBENZOYL)-PHOSPHINE OXIDE (CAS: 162881-26-7)

DNEL Workers - Inhalation; Long term, Short term systemic effects: 21 mg/m³
 Workers - Dermal; Long term, Short term systemic effects: 3.3 mg/kg
 Consumer - Inhalation; Long term systemic effects: 5.2 mg/m³
 Consumer - Dermal; Long term systemic effects: 1.5 mg/kg
 Consumer - Oral; Long term systemic effects: 1.5 mg/kg

2-HYDROXYETHYL METHACRYLATE (CAS: 868-77-9)

DNEL Industry - Dermal; systemic effects: 1.3 mg/m³
 Industry - Inhalation; systemic effects: 4.9 mg/m³
 Consumer - Dermal; systemic effects: 0.83 mg/m³
 Consumer - Inhalation; systemic effects: 2.9 mg/m³
 Consumer - Oral; systemic effects: 0.83 mg/m³

PNEC - Fresh water; 0.482 mg/l
 - marine water; 0.482 mg/l
 - STP; 10 mg/l
 - Intermittent release; 1 mg/l
 - Sediment (Freshwater); 3.79 mg/kg
 - Sediment (Marinewater); 3.79 mg/kg
 - Soil; 0.476 mg/l

2,6-di-tert-butyl-4-methylphenol (CAS: 128-37-0)

DNEL Industry - Inhalation; Long term systemic effects: 5.8 mg/m³
 Consumer - Inhalation; Long term systemic effects: 1.74 mg/m³
 Industry - Dermal; Long term systemic effects: 8.3 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 5 mg/kg/day

PNEC - Soil; 1.04 mg/kg
 - STP; 100 mg/l
 - Sediment; 1.29 mg/kg
 - marine water; 0.0004 mg/l
 - Intermittent release; 0.004 mg/l
 - Fresh water; 0.004 mg/l

2-BUTOXYETHYL ACETATE (CAS: 112-07-2)

Ingredient comments WEL = Workplace Exposure Limits

DNEL Industry - Inhalation; Long term systemic effects: 133 mg/m³
 Industry - Inhalation; Short term systemic effects: 775
 Industry - Inhalation; Short term local effects: 333 mg/m³
 Industry - Dermal; Long term systemic effects: 102 mg/kg/day
 Industry - Dermal; Short term systemic effects: 102 mg/kg/day

PNEC - Fresh water; .304 mg/l
 - marine water; .0304 mg/l
 - Intermittent release; .56 mg/l
 - STP; 90 mg/l
 - Sediment (Freshwater); 2.03 mg/kg
 - Sediment (Marinewater); .203 mg/kg
 - Soil; .68 mg/kg

EMP110/5140 W LED AS

2-METHYL-1-(4-METHYLTHIOPHENYL)-2-MORPHOLINOPROPAN-1-ONE (CAS: 71868-10-5)

DNEL	Workers - Inhalation; Long term systemic effects: 2.82 mg/m ³ Workers - Dermal; Long term systemic effects: 0.4 mg/kg/day General population - Dermal; Long term systemic effects: 0.2 mg/kg/day General population - Inhalation; Long term systemic effects: 0.7 mg/m ³
PNEC	Fresh water; .0172 mg/l marine water; .00172 mg/l Intermittent release; .016 mg/l Sediment (Freshwater); 1.13864 mg/kg Sediment (Marinewater); .113864 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear eye protection.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Butyl rubber. Nitrile rubber. Neoprene. Polyvinyl chloride (PVC). Laminate of polyethylene and ethylene vinyl alcohol (PE/EVOH).

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Do not eat, drink or smoke when using this product. Use engineering controls to reduce air contamination to permissible exposure level. Wash after use and before eating, smoking and using the toilet. Provide eyewash station. Wash contaminated clothing before reuse.

Respiratory protection

No specific requirements are anticipated under normal conditions of use.

Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	White.
Odour	Mild.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	78 deg C (based on lowest flash solvent)°C Setaflash closed cup.
Evaporation rate	Not determined.

EMP110/5140 W LED AS

Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.45 @ 25°C
Bulk density	Not determined.
Solubility(ies)	Immiscible with water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Kinematic viscosity > 20.5 mm ² /s.
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	No
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.
Comments	Information given is applicable to the product as supplied.
<u>9.2. Other information</u>	
Other information	None.
Refractive index	Not determined.
Particle size	Not applicable.
Molecular weight	Not applicable.
Volatility	Not determined.
Saturation concentration	Not determined.
Critical temperature	Not determined.
Volatile organic compound	Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

EMP110/5140 W LED AS

Conditions to avoid Keep away from heat, sparks and open flame. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Not determined.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not determined.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not determined.

Skin corrosion/irritation

Animal data No information available.

Human skin model test No information available.

Extreme pH Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met. Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Contains a substance/a group of substances which may damage fertility.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

EMP110/5140 W LED AS

Aspiration hazard	Based on available data the classification criteria are not met.
Inhalation	No specific health hazards known. May cause respiratory system irritation.
Ingestion	No specific health hazards known. May cause discomfort if swallowed.
Skin contact	May cause sensitisation by skin contact.
Eye contact	Causes serious eye irritation.
Acute and chronic health hazards	May cause skin sensitisation or allergic reactions in sensitive individuals. Suspected of damaging fertility.
Route of exposure	Inhalation Skin absorption Skin and/or eye contact Ingestion
Target organs	Reproductive organs
Medical symptoms	Symptoms following overexposure may include the following: Allergic rash.
Medical considerations	Allergic rash.

SECTION 12: Ecological information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms Not determined.

Acute toxicity - terrestrial Not determined.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not determined.

Short term toxicity - embryo and sac fry stages Not determined.

Chronic toxicity - aquatic invertebrates Not determined.

12.2. Persistence and degradability

Persistence and degradability This product is not expected to be readily biodegradable.

Phototransformation Not determined.

Stability (hydrolysis) Not determined.

Biodegradation Not determined.

Biological oxygen demand Not determined.

Chemical oxygen demand Not determined.

12.3. Bioaccumulative potential

EMP110/5140 W LED AS

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient Not determined.

12.4. Mobility in soil

Adsorption/desorption coefficient Not determined.

Henry's law constant Not determined.

Surface tension Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Transport labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

EMP110/5140 W LED AS

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. Health and Safety at Work etc. Act 1974 (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Health and environmental listings	None of the ingredients are listed.
Authorisations (Annex XIV Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Annex XVII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures according to Regulation (EC) 1272/2008	: Calculation method.
Issued by	ciw
Revision date	12/11/2019
Revision	3
Supersedes date	26/04/2018

EMP110/5140 W LED AS

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336 May cause drowsiness or dizziness.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H370 Causes damage to organs .
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.